## NSN 4720-00-009-9348



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-009-9348 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.219 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.484 inches **Minimum Inside Bending Radius:** 3.000 inches **Exterior Color:** Natural **Connection Style:** Swivel nut, flareless 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 2nd layer spirally laid corrosion resistant steel wire and outer layer braided corrosion resistant steel wire and 1st layer spirally laid corrosion resistant steel wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end

Seat Angle:

12.0 degrees 1st end

**Hydrostatic Test Pressure:** 

6000.0 pounds per square inch

**Outer Covering Environmental Protection:** 

Corrosion resistant

Inside Surface Condition:

Smooth

**Measuring Method And Length:** 

17.000 inches working

## NSN 4720-00-009-9348

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
---------	-----------

W/polytetrafluoroethylene external support

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0