

View Online at <https://aerobasegroup.com/nsn/4720-00-010-0564>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.438 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.649 inches

Minimum Inside Bending Radius:

3.500 inches

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

16 2nd end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

0.750 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

33.375 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Specification Data:

81349-mil-h-83796 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0

Mil-std (military Standard):

Mil-h-83796 spec.