

View Online at <https://aerobasegroup.com/nsn/4720-00-011-8511>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.447 inches and 0.570 inches

Temperature Rating:

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.718 inches and 0.789 inches

Minimum Inside Bending Radius:

3.005 inches

Connection Style:

Swivel nut, inverted flare 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Fitting Component And Surface Treatment:

Complete fitting passivate 1st end

Connection Type:

Threaded internal hose 2nd end

Thready Qty Per Inch (tpi):

16 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

1000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Maximum Operating Pressure:

400.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Hydrostatic Test Pressure:

600.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Mildew resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

19.008 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, buna-n

Media For Which Designed:

Ethylene glycol and water single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0