## NSN 4720-00-012-2229

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-012-2229

| One of Ocational Observa  |
|---|
| Cross Sectional Shape:  |
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.212 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response                                   |
| Outside Diameter:   |
| 0.507 inches  |
| Minimum Inside Bending Radius:  |
| 3.000 inches  |
| Exterior Color:   |
| Natural   |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Features Provided:  |
| Electrostatic discharge capability  |
| Burst Test Pressure:  |
| 16000.0 pounds per square inch  |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch   |
| Thread Size:  |
| 0.562 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 6000.0 pounds per square inch   |
| Outer Covering Environmental Protection:  |
| Corrosion resistant   |
| Inside Surface Condition:   |
| Smooth  |
| Massuring Method And Length:  |

26.000 inches working

## NSN 4720-00-012-2229

Nonmetallic Hose Assembly - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unf 1st end               |
| Shelf Life:               |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0