NSN 4720-00-015-9418

Shelf Life:

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-015-9418 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.310 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.670 inches **Minimum Inside Bending Radius:** 3.120 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided wire and outer layer rubber impregnated braided cotton cord and 1st layer braided textile yarn **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Flow Angle: 90.0 degrees 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 16.500 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end

NSN 4720-00-015-9418

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0