NSN 4720-00-018-2293

Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-018-2293 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -67.0 degrees fahrenheit and 158.0 degrees fahrenheit single response **Outside Diameter:** 0.781 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **End Fitting Component And Material:** Complete fitting aluminum alloy all ends **Connection Type:** Threaded internal tube 1st end **Second End Relationship With First End:** Identical **Burst Test Pressure:** 750.0 pounds per square inch First End Swivel Action Capability: Not included **Layer Composition And Location:** Outer layer molded rubber **Maximum Operating Pressure:** 150.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle:

37.0 degrees 1st end **Hydrostatic Test Pressure:** 250.0 pounds per square inch **Vacuum In Torr:** 508.0 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 300.000 inches working

NSN 4720-00-018-2293

Nonmetallic Hose Assembly - Page 2 of 2



Inner conveying tube material-rubber, synthetic

Thread Series Designator:

Unf 1st end

Specification Data:

88044-an6270 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0