Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-019-0323

c	ross Sectional Shape:
	ound
	hread Class:
	o 1st end
-	hread Direction:
	ight-hand 1st end
	190 inches
-	
	empurature Rating: 5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
	utside Diameter:
-	
	310 inches
	inimum Inside Bending Radius:
	000 inches
	onnection Style:
	wivel nut flare 2nd end
	nd Connection Design:
	traight 1st end
	onnection Type:
	hreaded internal tube 1st end
	urst Test Pressure:
	2000.0 pounds per square inch
	ayer Composition And Location:
	uter layer braided corrosion resistant steel wire
	aximum Operating Pressure:
	500.0 pounds per square inch
	hread Size:
-	438 inches 1st end
	eat Angle:
	7.0 degrees 2nd end
	low Angle:
90	0.0 degrees 2nd end
In	side Surface Condition:
Sı	mooth
S	pecial Features:
	onsists of 3.910 in.Sleeve
TI	hread Series Designator:
U	nf 2nd end
S	helf Life:
N	/a
U	nit Of Measure:

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

