NSN 4720-00-020-8567

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-020-8567

Cross Sectional Shape:					
Round					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.375 inches					
Tempurature Rating:					
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response					
Minimum Inside Bending Radius:					
5.000 inches					
Connection Style:					
Plain optional end 1st end					
End Connection Design:					
Straight 2nd end					
Connection Type:					
Threaded internal pipe 1st end					
Features Provided:					
Electrostatic discharge capability					
Burst Test Pressure:					
16000.0 pounds per square inch					
Layer Composition And Location:					
2nd layer braided steel wire and outer layer molded rubber, synthetic and 1st layer braided steel wire					
Maximum Operating Pressure:					
4000.0 pounds per square inch					
Thread Size:					
0.375 inches 1st end					
Seat Angle:					
30.0 degrees 2nd end					
Hydrostatic Test Pressure:					
8000.0 pounds per square inch					
Outer Covering Environmental Protection:					
Incombustible and weatherproof					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
15.000 inches					
Media For Which Designed:					
Fuel/oil, hydrocarbon and hydraulic fluid and grease and water, fresh single response					
Thread Series Designator:					
Nptf 2nd end					
Shelf Life:					
N/a					

NSN 4720-00-020-8567

Nonmetallic Hose Assembly - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A542a0