## NSN 4720-00-022-1659

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-022-1659

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.313 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.546 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Black
Quick Disconnect Size:
0.250 inches 2nd end
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
1600.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided rayon cord
Maximum Operating Pressure:
400.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
17.000 inches

Media For Which Designed:
Air and fuel/oil, hydrocarbon single response

## NSN 4720-00-022-1659

Nonmetallic Hose Assembly - Page 2 of 2



				_			
Ιh	roa	ď	Serie	26 I J	Dein	ın ətr	٦r٠

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0