Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-022-2472

| view Online at https://aerobasegroup.com/nsn/4720-00-022-2472 |
|---|
| Cross Sectional Shape: |
| Round |
| Inside Diameter: |
| 0.500 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 150.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.075 inches |
| Minimum Inside Bending Radius: |
| 3.000 inches |
| Exterior Color: |
| Black |
| Quick Disconnect Size: |
| 0.500 inches 1st end |
| Connection Style: |
| Push (internal) 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Internal quick disconnect 1st end |
| Burst Test Pressure: |
| 800.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided rayon cord and outer layer molded rubber, buna-s |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Abrasion resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 43.000 inches |
| Media For Which Designed: |
| Air single response and water single response and chemicals single response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |
| |