Nonmetallic Hose Assembly - Page 1 of 2



, 3
View Online at https://aerobasegroup.com/nsn/4720-00-022-9343
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-100.0 degrees fahrenheit and 450.0 degrees fahrenheit single response
Outside Diameter:
1.109 inches
Minimum Inside Bending Radius:
7.375 inches
Angle Between Rigid Elbow Fittings In Deg:
320.0
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1250.0 pounds per square inch
Thread Size:
1.312 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth



Measuring Method And Length:

41.000 inches working

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0