

View Online at <https://aerobasegroup.com/nsn/4720-00-025-0782>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.173 inches and 0.188 inches

Outside Diameter:

0.469 inches

Minimum Inside Bending Radius:

1.500 inches

Inner Conveying Tube Style:

Annular close-pitch corrugated

Exterior Color:

Natural

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Layer Composition And Location:

Outer layer braided bronze wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant

Measuring Method And Length:

180.000 inches

Media For Which Designed:

Hydraulic fluid and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Fsc Application Data:

Explosives, bulk propellants and explosive devices

Reference Number Differentiating Characteristics:

1 moisture-vapor proof barrier bag, 10 water resistant fiber cartons

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0