

View Online at <https://aerobasegroup.com/nsn/4720-00-025-9375>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.625 inches

**Temperature Rating:**

-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

**Flange Thickness:**

0.281 inches 2nd end and 0.313 inches 2nd end

**Outside Diameter:**

0.797 inches

**Minimum Inside Bending Radius:**

6.500 inches

**Center To Center Distance Between Bolt Holes Along Width:**

0.951 inches 2nd end

**Center To Center Distance Between Bolt Holes Along Length:**

0.951 inches 2nd end

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

1.594 inches 2nd end and 1.610 inches 2nd end

**Flange Width:**

1.594 inches 1st end and 1.610 inches 1st end

**Connection Style:**

Raised swivel 2nd end

**Bolt Hole Diameter:**

0.205 inches 2nd end

**Raised Face Height:**

0.020 inches 2nd end

**Raised Face Diameter:**

1.245 inches 2nd end and 1.250 inches 2nd end

**End Flange Construction:**

Split 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Raised face flange 2nd end

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

6000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Abrasion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

11.500 inches working and 11.750 inches working

**Flange Style:**

Rectangular (includes square) 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0