

View Online at <https://aerobasegroup.com/nsn/4720-00-025-9375>

Cross Sectional Shape:

Round

Inside Diameter:

0.625 inches

Temperature Rating:

-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Flange Thickness:

0.281 inches 2nd end and 0.313 inches 2nd end

Outside Diameter:

0.797 inches

Minimum Inside Bending Radius:

6.500 inches

Center To Center Distance Between Bolt Holes Along Width:

0.951 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

0.951 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

1.594 inches 2nd end and 1.610 inches 2nd end

Flange Width:

1.594 inches 1st end and 1.610 inches 1st end

Connection Style:

Raised swivel 2nd end

Bolt Hole Diameter:

0.205 inches 2nd end

Raised Face Height:

0.020 inches 2nd end

Raised Face Diameter:

1.245 inches 2nd end and 1.250 inches 2nd end

End Flange Construction:

Split 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Raised face flange 2nd end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

11.500 inches working and 11.750 inches working

Flange Style:

Rectangular (includes square) 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0