

View Online at <https://aerobasegroup.com/nsn/4720-00-030-1681>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.391 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

**Outside Diameter:**

0.765 inches

**Minimum Inside Bending Radius:**

5.300 inches

**Angle Between Rigid Elbow Fittings In Deg:**

270.0

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

12000.0 pounds per square inch

**Layer Composition And Location:**

2nd layer spirally laid steel wire and outer layer braided corrosion resistant steel wire and 1st layer spirally laid steel wire

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant and fire retardant and fuel resistant and hydraulic solution resistant and light resistant and mildew resistant and oil resistant and ozone resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

15.875 inches working

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved source, 50599, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A542a0