

View Online at <https://aerobasegroup.com/nsn/4720-00-031-7593>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.921 inches

Minimum Inside Bending Radius:

5.500 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

7000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord

Maximum Operating Pressure:

1750.0 pounds per square inch

Thread Size:

0.875 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3500.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and mildew resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

26.250 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms28741 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0