NSN 4720-00-032-4876

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-032-4876 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** Between 0.485 inches and 0.531 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 156.0 degrees fahrenheit single response **Outside Diameter:** Between 0.875 inches and 0.947 inches **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal pipe 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and outer layer molded rubber, chloroprene **Thread Size:** 0.500 inches 2nd end **Hydrostatic Test Pressure:** 4000.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant and light resistant and oil resistant and ozone resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 130.000 inches Media For Which Designed: Air and fuel/oil, hydrocarbon single response **Thread Series Designator:** Nptf 2nd end Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 4720-00-032-4876

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0