Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-032-4977

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.625 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.078 inches |
| Minimum Inside Bending Radius: |
| 6.562 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Burst Test Pressure: |
| 6000.0 pounds per square inch |
| Layer Composition And Location: |
| 2nd layer braided steel wire and outer layer rubber impregnated braided fabric and 1st layer braided fabric |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |
| 1.062 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Vacuum In Torr: |
| 50.8 |
| Inside Surface Condition: |
| |
| Measuring Method And Length: |
| 17.000 inches |
| Special Features: |
| Adapter, jic male flare to female, sil braze, pipe |
| Thread Series Designator: |
| Un 1st end |

NSN 4720-00-032-4977

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

