Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-033-8860

Cross Se	ctional Shape:
Round	
Thread C	lass:
3b 1st end	ł
Thread D	irection:
Right-han	d 1st end
Inside Dia	ameter:
0.188 incł	nes
Tempura	ture Rating:
-65.0 deg	rees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside [Diameter:
0.312 incl	nes
Minimum	Inside Bending Radius:
2.000 incl	nes
Connecti	on Style:
Swivel nu	t flare 2nd end
End Con	nection Design:
Straight 1	st end
Connecti	on Type:
Threaded	internal tube 1st end
Burst Tes	st Pressure:
7000.0 pc	unds per square inch
Layer Co	mposition And Location:
Outer laye	er braided corrosion resistant steel wire
Maximum	Operating Pressure:
1500.0 pc	unds per square inch
Thread S	ize:
0.438 incł	nes 1st end
Seat Ang	le:
37.0 degr	ees 2nd end
Hydrosta	tic Test Pressure:
3000.0 pc	unds per square inch
Flow Ang	le:
90.0 degr	ees 2nd end
Inside Su	rface Condition:
Smooth	
Measurin	g Method And Length:
10.000 ind	ches working
Thread S	eries Designator:
Unjf 1st e	nd
Shelf Life	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0