NSN 4720-00-034-7813

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-034-7813

Inside Diameter:
6.000 inches
Bolt Circle Diameter:
9.500 inches 1st end
Bolt Hole Quantity:
8 1st end
Connection Style:
Plain 1st end
Bolt Hole Diameter:
0.750 inches 1st end
End Flange Construction:
Solid 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting copper alloy all ends
Connection Type:
Plain face flange 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
600.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Layer Composition And Location: 1st layer molded rubber, chloroprene
1st layer molded rubber, chloroprene
1st layer molded rubber, chloroprene Maximum Operating Pressure:
1st layer molded rubber, chloroprene Maximum Operating Pressure: 150.0 pounds per square inch
1st layer molded rubber, chloroprene Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure:
1st layer molded rubber, chloroprene Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 250.0 pounds per square inch
1st layer molded rubber, chloroprene Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 250.0 pounds per square inch Vacuum In Torr:
1st layer molded rubber, chloroprene Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 250.0 pounds per square inch Vacuum In Torr: 254.0
1st layer molded rubber, chloroprene Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 250.0 pounds per square inch Vacuum In Torr: 254.0 Inside Surface Condition:
1st layer molded rubber, chloroprene Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 250.0 pounds per square inch Vacuum In Torr: 254.0 Inside Surface Condition: Smooth
1st layer molded rubber, chloroprene Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 250.0 pounds per square inch Vacuum In Torr: 254.0 Inside Surface Condition: Smooth Measuring Method And Length:

Special Features:

Inner conveying tube material-rubber, synthetic

NSN 4720-00-034-7813

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:
Fuel/oil, hydrocarbon single response
Specification Data:
81349-mil-h-17505 government specification
Specification Or Standard:
6 size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0