NSN 4720-00-034-8512

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-034-8512

| Cross Sectional Shape: |
|--|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.500 inches |
| Outside Diameter: |
| 0.875 inches |
| Connection Style: |
| Inverted flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Burst Test Pressure: |
| 3200.0 pounds per square inch |
| Layer Composition And Location: |
| 2nd layer braided rayon cord and outer layer molded rubber, synthetic and 1st layer braided rayon cord |
| Maximum Operating Pressure: |
| 800.0 pounds per square inch |
| Thread Size: |
| 0.500 inches 1st end |
| Seat Angle: |
| 30.0 degrees 1st end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 144.000 inches |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Nptf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| <u></u> |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |