## NSN 4720-00-035-8072

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-035-8072

Cross Sectional Shape: Round Thread Direction: Right-hand 1st end Inside Dlameter: Between 0.242 inches and 0.273 inches Tempurature Rating: -67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: Between 0.594 inches and 0.656 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuelvoii, hydrocarbon single response Thread Series Designator: Net test and	View Online at https://aerobasegroup.com/nsn/4720-00-035-8072
Thread Direction: Right-hand 1st end Inside Diameter: Between 0.242 inches and 0.273 inches Tempurature Rating: -67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: Between 0.594 inches and 0.656 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	Cross Sectional Shape:
Right-hand 1st end Inside Diameter: Between 0.242 inches and 0.273 inches Tempurature Rating: -67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: Between 0.594 inches and 0.656 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	Round
Inside Diameter: Between 0.242 inches and 0.273 inches Tempurature Rating: -67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: Between 0.594 inches and 0.656 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	Thread Direction:
Between 0.242 inches and 0.273 inches  Tempurature Rating: -67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response  Outside Diameter: Between 0.594 inches and 0.656 inches  Minimum Inside Bending Radius: 4.000 inches  Connection Style: Inverted flare 1st end  End Connection Design: Straight 1st end  Connection Type: Threaded external pipe 1st end  Burst Test Pressure: 11000.0 pounds per square inch  Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire  Maximum Operating Pressure: 2750.0 pounds per square inch  Thread Size: 0.250 inches 1st end  Bydrostatic Test Pressure: 5500.0 pounds per square inch  Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth  Measuring Method And Length: 124.000 inches  Media For Which Designed: Fuel/oil, hydrocarbon single response  Thread Series Designator:	Right-hand 1st end
Tempurature Rating: -67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response  Outside Diameter: Between 0.594 inches and 0.656 inches  Minimum Inside Bending Radius: 4.000 inches  Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end  Connection Type: Threaded external pipe 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire  Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	Inside Diameter:
-67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response  Outside Diameter:  Between 0.594 inches and 0.656 inches  Minimum Inside Bending Radius: 4.000 inches  Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire  Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	Between 0.242 inches and 0.273 inches
Outside Diameter: Between 0.594 inches and 0.656 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	Tempurature Rating:
Between 0.594 inches and 0.656 inches  Minimum Inside Bending Radius: 4.000 inches  Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	-67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Minimum Inside Bending Radius: 4.000 inches Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	Outside Diameter:
Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	Between 0.594 inches and 0.656 inches
Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	Minimum Inside Bending Radius:
Inverted flare 1st end  End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	4.000 inches
End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	Connection Style:
Straight 1st end  Connection Type: Threaded external pipe 1st end  Burst Test Pressure: 11000.0 pounds per square inch  Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire  Maximum Operating Pressure: 2750.0 pounds per square inch  Thread Size: 0.250 inches 1st end  Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure: 5500.0 pounds per square inch  Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth  Measuring Method And Length: 124.000 inches  Media For Which Designed: Fuel/oil, hydrocarbon single response  Thread Series Designator:	Inverted flare 1st end
Connection Type: Threaded external pipe 1st end Burst Test Pressure: 11000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	End Connection Design:
Threaded external pipe 1st end  Burst Test Pressure:  11000.0 pounds per square inch  Layer Composition And Location:  Outer layer molded rubber and 1st layer braided steel wire  Maximum Operating Pressure:  2750.0 pounds per square inch  Thread Size:  0.250 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:  5500.0 pounds per square inch  Outer Covering Environmental Protection:  Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:  124.000 inches  Media For Which Designed:  Fuel/oil, hydrocarbon single response  Thread Series Designator:	Straight 1st end
Burst Test Pressure:  11000.0 pounds per square inch  Layer Composition And Location:  Outer layer molded rubber and 1st layer braided steel wire  Maximum Operating Pressure:  2750.0 pounds per square inch  Thread Size:  0.250 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:  5500.0 pounds per square inch  Outer Covering Environmental Protection:  Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition:  Smooth  Measuring Method And Length:  124.000 inches  Media For Which Designed:  Fuel/oil, hydrocarbon single response  Thread Series Designator:	Connection Type:
11000.0 pounds per square inch  Layer Composition And Location:  Outer layer molded rubber and 1st layer braided steel wire  Maximum Operating Pressure:  2750.0 pounds per square inch  Thread Size:  0.250 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:  5500.0 pounds per square inch  Outer Covering Environmental Protection:  Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:  124.000 inches  Media For Which Designed:  Fuel/oil, hydrocarbon single response  Thread Series Designator:	Threaded external pipe 1st end
Layer Composition And Location: Outer layer molded rubber and 1st layer braided steel wire  Maximum Operating Pressure: 2750.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	Burst Test Pressure:
Outer layer molded rubber and 1st layer braided steel wire  Maximum Operating Pressure:  2750.0 pounds per square inch  Thread Size:  0.250 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:  5500.0 pounds per square inch  Outer Covering Environmental Protection:  Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:  124.000 inches  Media For Which Designed:  Fuel/oil, hydrocarbon single response  Thread Series Designator:	11000.0 pounds per square inch
Maximum Operating Pressure:  2750.0 pounds per square inch  Thread Size:  0.250 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:  5500.0 pounds per square inch  Outer Covering Environmental Protection:  Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition:  Smooth  Measuring Method And Length:  124.000 inches  Media For Which Designed:  Fuel/oil, hydrocarbon single response  Thread Series Designator:	Layer Composition And Location:
2750.0 pounds per square inch  Thread Size:  0.250 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:  5500.0 pounds per square inch  Outer Covering Environmental Protection:  Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:  124.000 inches  Media For Which Designed:  Fuel/oil, hydrocarbon single response  Thread Series Designator:	Outer layer molded rubber and 1st layer braided steel wire
Thread Size:  0.250 inches 1st end  Seat Angle:  30.0 degrees 1st end  Hydrostatic Test Pressure:  5500.0 pounds per square inch  Outer Covering Environmental Protection:  Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:  124.000 inches  Media For Which Designed:  Fuel/oil, hydrocarbon single response  Thread Series Designator:	Maximum Operating Pressure:
0.250 inches 1st end  Seat Angle: 30.0 degrees 1st end  Hydrostatic Test Pressure: 5500.0 pounds per square inch  Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth  Measuring Method And Length: 124.000 inches  Media For Which Designed: Fuel/oil, hydrocarbon single response  Thread Series Designator:	2750.0 pounds per square inch
Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 5500.0 pounds per square inch Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	Thread Size:
30.0 degrees 1st end  Hydrostatic Test Pressure: 5500.0 pounds per square inch  Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth  Measuring Method And Length: 124.000 inches  Media For Which Designed: Fuel/oil, hydrocarbon single response  Thread Series Designator:	0.250 inches 1st end
Hydrostatic Test Pressure:  5500.0 pounds per square inch  Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth  Measuring Method And Length: 124.000 inches  Media For Which Designed: Fuel/oil, hydrocarbon single response  Thread Series Designator:	Seat Angle:
5500.0 pounds per square inch  Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth  Measuring Method And Length: 124.000 inches  Media For Which Designed: Fuel/oil, hydrocarbon single response  Thread Series Designator:	30.0 degrees 1st end
Outer Covering Environmental Protection: Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	Hydrostatic Test Pressure:
Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 124.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	5500.0 pounds per square inch
Inside Surface Condition:  Smooth  Measuring Method And Length:  124.000 inches  Media For Which Designed:  Fuel/oil, hydrocarbon single response  Thread Series Designator:	Outer Covering Environmental Protection:
Smooth  Measuring Method And Length: 124.000 inches  Media For Which Designed: Fuel/oil, hydrocarbon single response  Thread Series Designator:	Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant
Measuring Method And Length: 124.000 inches  Media For Which Designed: Fuel/oil, hydrocarbon single response  Thread Series Designator:	Inside Surface Condition:
124.000 inches  Media For Which Designed:  Fuel/oil, hydrocarbon single response  Thread Series Designator:	Smooth
Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:	Measuring Method And Length:
Fuel/oil, hydrocarbon single response  Thread Series Designator:	124.000 inches
Fuel/oil, hydrocarbon single response  Thread Series Designator:	Media For Which Designed:
Thread Series Designator:	-
-	
NPL 1St end	Npt 1st end
Shelf Life:	
N/a	N/a

## NSN 4720-00-035-8072

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0