Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-035-8076

| Cross Sectional Shape: | |
|--|--|
| Round | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| Between 0.242 inches and 0.273 inches | |
| Tempurature Rating: | |
| -67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response | |
| Outside Diameter: | |
| Between 0.594 inches and 0.656 inches | |
| Minimum Inside Bending Radius: | |
| 4.000 inches | |
| Connection Style: | |
| Inverted flare 1st end | |
| End Connection Design: | |
| Straight 1st end | |
| Connection Type: | |
| Threaded external pipe 1st end | |
| Burst Test Pressure: | |
| 11000.0 pounds per square inch | |
| Layer Composition And Location: | |
| Outer layer molded rubber and 1st layer braided steel wire | |
| Maximum Operating Pressure: | |
| 2750.0 pounds per square inch | |
| Thread Size: | |
| 0.250 inches 1st end | |
| Seat Angle: | |
| 30.0 degrees 1st end | |
| Hydrostatic Test Pressure: | |
| 5500.0 pounds per square inch | |
| Outer Covering Environmental Protection: | |
| Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant | |
| Inside Surface Condition: | |
| Smooth | |
| Measuring Method And Length: | |
| 54.000 inches | |
| Media For Which Designed: | |
| Fuel/oil, hydrocarbon single response | |
| Thread Series Designator: | |
| Npt 1st end | |
| Shelf Life: | |
| N/a | |
| | |

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0