## NSN 4720-00-035-8082

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-035-8082

| view Online at https://aerobasegroup.com/hsn/4720-00-055-8082                            |
|--|
| Cross Sectional Shape:   |
| Round  |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| Between 0.242 inches and 0.273 inches  |
| Tempurature Rating:  |
| -67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response                    |
| Outside Diameter:  |
| Between 0.594 inches and 0.656 inches  |
| Minimum Inside Bending Radius:   |
| 4.000 inches   |
| Connection Style:  |
| Inverted flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded external pipe 1st end   |
| Burst Test Pressure:   |
| 11000.0 pounds per square inch   |
| Layer Composition And Location:  |
| Outer layer molded rubber, chloroprene and 1st layer braided steel wire                  |
| Maximum Operating Pressure:  |
| 2750.0 pounds per square inch  |
| Thread Size:   |
| 0.250 inches 1st end   |
| Seat Angle:  |
| 30.0 degrees 1st end   |
| Hydrostatic Test Pressure:   |
| 5500.0 pounds per square inch  |
| Outer Covering Environmental Protection:   |
| Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 12.500 inches  |
| Media For Which Designed:  |
| Fuel/oil, hydrocarbon single response  |
| Thread Series Designator:  |
| Nptf 1st end   |
| Shelf Life:  |
|  |

N/a

## NSN 4720-00-035-8082

Nonmetallic Hose Assembly - Page 2 of 2



|    | • • |             |     |     |      |
|----|-----|-------------|-----|-----|------|
| In | 18  | <i>(</i> )+ | МЛО | 201 | ure: |
|    |     |             |     |     |      |

--

Demilitarization:

No

Fiig:

A542a0