NSN 4720-00-035-8089

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-035-8089 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.406 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.765 inches **Connection Style:** Inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** Outer layer rubber impregnated braided cotton cord and 1st layer braided steel wire **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end **Hydrostatic Test Pressure:** 4000.0 pounds per square inch **Outer Covering Environmental Protection:** Hydraulic solution resistant and cold resistant and mildew resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 190,000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Npt 1st end Shelf Life: N/a **Unit Of Measure:**

--

NSN 4720-00-035-8089

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0