NSN 4720-00-035-8094

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-035-8094

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.610 inches and 0.656 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
Between 1.000 inches and 1.062 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided steel wire and 1st layer braided cotton cord
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Hydraulic solution resistant and cold resistant and mildew resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
23.000 inches
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

-

NSN 4720-00-035-8094

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0