Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-035-8099

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 1.797 inches and 1.869 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
Between 2.352 inches and 2.476 inches
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Thready Qty Per Inch (tpi):
11-1/2 1st end
Burst Test Pressure:
1500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided steel wire and 1st layer braided cotton cord
Maximum Operating Pressure:
375.0 pounds per square inch
Thread Size:
2.000 inches 1st end
Hydrostatic Test Pressure:
750.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
16.500 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Nptf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4720-00-035-8099

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

