NSN 4720-00-035-8985

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-035-8985 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.313 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response **Outside Diameter:** 0.672 inches **Minimum Inside Bending Radius:** 4.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord **Maximum Operating Pressure:** 2250.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Outer Covering Environmental Protection:** Fuel resistant and oil resistant Vacuum In Torr: 50.8 **Inside Surface Condition:** Smooth

Measuring Method And Length:

65.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

NSN 4720-00-035-8985

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0