Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-036-6201

Cross Sectional Shape: Round Thread Class: 3b Ist end Thread Direction: Right-hand 1st end Inside Diameter: 0.313 inches Tempurature Rating: e5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: Between 0.422 inches and 0.469 inches Minimun Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Quy Per Inch (tpi): 18 1st end Surst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 0.562 inches 2nd end Maximum Operating Pressure: 0.562 inches 2nd end Maximum Operating Pressure: 0.562 inches 2nd end Maximum Operating Pressure:<		
Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.313 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: Between 0.422 inches and 0.469 inches Minimun Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Peruse Provided: Electrostatic discharge capability Thread dinternal tube 1st end Fatures Provided: Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.3.0 pounds per square inch Hydrostatic Test Pressure: 150.0.0 pounds per square inch Hared Size: 0.3.0 pounds per square inch Hydrostatic Test Pressure: 13.0 degrees 2nd end <	Cross Sectional Shape:	
3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.313 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: Between 0.422 inches and 0.469 inches Minnum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Peatures Provided: Electrostatic discharge capability Thready dty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: Outre layer braided corrosion resistant steel wire Maximum Operating Pressure: 150.0 pounds per square inch Straiget 0.552 inches 2nd end Straiget Test Pressure: 150.0.0 pounds per square inch Hare Straiget Test Pressure: 150.0.0 pounds per square inch Hare Straiget Test Pressure: 150.0.0 pounds per square inch Hare Straiget Test Pressure:	Round	
Thread Direction: Right-hand 1st end Inside Diameter: 0.313 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: Between 0.422 inches and 0.469 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Thready dty Per Inch (tpl): 18 1st end Burst Test Pressure: 0000.0 pounds per square inch Layer Composition And Location: 0xole partial pressure: 150.00 pounds per square inch Externel Size: 0.552 inches 2nd end Straight 3t end Burst Test Pressure: 1500.0 pounds per square inch Layer Composition And Location: 0.552 inches 2nd end Maximum Operating Pressure: 150.00 pounds per square inch Hread Size: 0.552 inches 2nd end Statagle: 3.00.0 pounds per square inch	Thread Class:	
Right-hand 1st end Inside Diameter: 0.313 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: Between 0.422 inches and 0.469 inches Minimun Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Porneetion Type: Threaded internal tube 1st end Features Provided: Electostatic discharge capability Thready Qty Per Inch (tpi): 18 1st end 9000.0 pounds per square inch Layer Composition And Location: Outer I ayer braided corrosion resistant steel wire Maximun Operating Pressure: 150.0 pounds per square inch Electiones 2nd end Maximun Operating Pressure: 0.562 inches 2nd end Myrostatic Test Pressure: 0.502 inches 2nd end Muros per square inch Fuer Asile: 0.562 inches 2nd end Myrostatic Test Pressure: 0.500.0 pounds per square inch	3b 1st end	
Inside Diameter: 0.313 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: Between 0.422 inches and 0.469 inches Minimun Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Threaded special capability 18 1st end 9000.0 pounds per square inch Layer Composition And Location: 0uter layer braided corrosion resistant steel wire Maximun Operating Pressure: 9300.0 pounds per square inch Electrostatic Test Pressure: 0.562 inches 2nd end Hydrostatic Test Pressure: 0.562 inches 2nd end Maximun Operating Pressure: 0.300.0 pounds per square inch Fuer and Size: 0.562 inches 2nd end Murpetsion And Location: 0.562 inches 2nd end Murpetsion Test Pressur	Thread Direction:	
0.313 inchesFampurature Rating:65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single responseOutside Diameter:Between 0.422 inches and 0.469 inchesMinimun Inside Bending Radius:4.000 inchesConnection Style:Swivel nut flare 2nd endEnd Connection Design:Straight 1st endPonection Type:Threaded internal tube 1st endFeatures Provide:Electrostatic discharge capabilityThready Qty Per Inch (tpi):18 1st end9000.0 pounds per square inchLayer Composition And Location:0uter layer braided corrosion resistant steel wireMaximun Operating Pressure:150.0.0 pounds per square inchStried Size:0.562 inches 2nd endMaximun Operating Pressure:150.0.0 pounds per square inchFuread Size:0.562 inches 2nd endMydrostatic Test Pressure:0.502 inches 2nd endMaximun Operating Pressure:0.502 inches 2nd endMydrostatic Test Pressure:0.502 inches 2nd endMydrostatic Test Pressure:0.500.0 pounds per square inchFuer Angle:0.502 inches 2nd endMydrostatic Test Pressure:0.502 inches 2nd end <td< td=""><td>Right-hand 1st end</td><td></td></td<>	Right-hand 1st end	
Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: Between 0.422 inches and 0.469 inches Minimum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 150.0.0 pounds per square inch Straige: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Furend Size: 0.562 inches 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Furend Size: 0.502 inches 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch </td <td>Inside Diameter:</td> <td></td>	Inside Diameter:	
- 65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: Between 0.422 inches and 0.469 inches Minimun Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 18 Ist end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 0.562 inches 2nd end Steat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Fuer Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Mydrostatic Test Pressure: </td <td>0.313 inches</td> <td></td>	0.313 inches	
Outside Diameter:Between 0.422 inches and 0.469 inchesMinimun Inside Bending Radius:4.000 inchesConnection Style:Swivel nut flare 2nd endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityThready Qty Per Inch (tpi):18 Ist endBurst Test Pressure:9000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:0.562 inches 2nd endStol97.0 degrees 2nd endHydrostatic Test Pressure:0.500.0 pounds per square inchEntred Size:0.562 inches 2nd endMaximum Operating Pressure:0.562 inches 2nd endMydrostatic Test Pressure:0.500.0 pounds per square inchEntred Size:0.562 inches 2nd endMydrostatic Test Pressure:0.500.0 pounds per square inchFured Size:0.562 inches 2nd endMydrostatic Test Pressure:0.500.0 pounds per square inchFlow Angle:0.0 degrees 2nd end0.0 degrees 2nd end <td>Tempurature Rating:</td> <td></td>	Tempurature Rating:	
Between 0.422 inches and 0.469 inches Minimun Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximun Operating Pressure: 1500.0 pounds per square inch Straige: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Flow Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 300.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end	-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response	
Minimum Inside Bending Radius: 4.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Steat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 300.0.0 pounds per square inch Furead Size: 0.0 degrees 2nd end Outer Covering Environmental Protection:	Outside Diameter:	
 4.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 0.562 inches 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Entre Argle: 3000.0 pounds per square inch Forw Angle: 90.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Conter Covering Environmental Protection: 	Between 0.422 inches and 0.469 inches	
Connection Style:Swivel nut flare 2nd endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityThready Qty Per Inch (tpi):18 1st endBurst Test Pressure:9000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchSteat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchFine Angle:3000.0 pounds per square inchFine Angle:90.0 degrees 2nd endFlow Angle:90.0 degrees 2nd endFlow Angle:90.0 degrees 2nd endOuter Covering Environmental Protection:	Minimum Inside Bending Radius:	
Swivel nut flare 2nd endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityThready Qty Per Inch (tpi):18 1st endBurst Test Pressure:9000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchEntread Size:0.562 inches 2nd endSeat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchFlow Angle:900.0 pounds per square inch	4.000 inches	
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Hydrostatic Test Pressure: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0. degrees 2nd end Conserver inch	Connection Style:	
Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Fiow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection:	Swivel nut flare 2nd end	
Connection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityThready Qty Per Inch (tpi):18 1st endBurst Test Pressure:9000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.562 inches 2nd endSeat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchFlow Angle:90.0 degrees 2nd endCouter Covering Environmental Protection:	End Connection Design:	
Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Poure Covering Environmental Protection:	Straight 1st end	
Features Provided:Electrostatic discharge capabilityElectrostatic discharge capabilityThready Qty Per Inch (tpi):18 1st endBurst Test Pressure:9000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.562 inches 2nd endSeat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchFlow Angle:90.0 degrees 2nd endHudrostatic Test Pressure:90.0 degrees 2nd endHydrostatic Test Pressure:90.0 degrees 2nd endHour Layer	Connection Type:	
Electrostatic discharge capability Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection:	Threaded internal tube 1st end	
Thready Qty Per Inch (tpi):18 1st endBurst Test Pressure:9000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.562 inches 2nd endSeat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchFlow Angle:90.0 degrees 2nd endOuter Covering Environmental Protection:	Features Provided:	
 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: 	Electrostatic discharge capability	
Burst Test Pressure:9000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.562 inches 2nd endSeat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchFlow Angle:90.0 degrees 2nd endOuter Covering Environmental Protection:	Thready Qty Per Inch (tpi):	
 9000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: 	18 1st end	
Layer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.562 inches 2nd endSeat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchFlow Angle:90.0 degrees 2nd endOuter Covering Environmental Protection:	Burst Test Pressure:	
Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.562 inches 2nd endSeat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchFlow Angle:90.0 degrees 2nd endOuter Covering Environmental Protection:	9000.0 pounds per square inch	
Maximum Operating Pressure:1500.0 pounds per square inchThread Size:0.562 inches 2nd endSeat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchFlow Angle:90.0 degrees 2nd endOuter Covering Environmental Protection:	Layer Composition And Location:	
 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: 	Outer layer braided corrosion resistant steel wire	
Thread Size:0.562 inches 2nd endSeat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchFlow Angle:90.0 degrees 2nd endOuter Covering Environmental Protection:	Maximum Operating Pressure:	
0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection:	1500.0 pounds per square inch	
Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection:	Thread Size:	
 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: 	0.562 inches 2nd end	
Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection:	Seat Angle:	
3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection:	37.0 degrees 2nd end	
Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection:	Hydrostatic Test Pressure:	
90.0 degrees 2nd end Outer Covering Environmental Protection:	3000.0 pounds per square inch	
Outer Covering Environmental Protection:	Flow Angle:	
-	90.0 degrees 2nd end	
Corrosion resistant and fuel resistant	Outer Covering Environmental Protection:	
	Corrosion resistant and fuel resistant	
Vacuum In Torr:	Vacuum In Torr:	
50.8	50.8	

NSN 4720-00-036-6201

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:

Smooth

Media For Which Designed:

Air single response and hydraulic fluid single response and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0