## NSN 4720-00-040-0999

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-040-0999

Cross Sectional Change
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
2.000 inches
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Thready Qty Per Inch (tpi):
11-1/2 1st end
Burst Test Pressure:
6500.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and outer layer molded rubber, synthetic and 1st layer braided steel wire
Maximum Operating Pressure:
1625.0 pounds per square inch
Thread Size:
1.250 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
3250.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and hydraulic solution resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
30.250 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Nptf 1st end
Shelf Life:

N/a

## NSN 4720-00-040-0999

Nonmetallic Hose Assembly - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0