Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-042-7243

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.530 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings and nonskive
Burst Test Pressure:
11000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided corrosion resistant steel wire
Maximum Operating Pressure:
2750.0 pounds per square inch
Thread Size:
0.536 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
5500.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:

16.000 inches

NSN 4720-00-042-7243

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Hydraulic fluid, water base single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0