Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-043-0899

Cross Sectional Shape:
Round
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.440 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 160.0 degrees fahrenheit single response
Outside Diameter:
0.720 inches
Minimum Inside Bending Radius:
5.000 inches
Exterior Color:
Natural
Connection Style:
Swivel nut double compression 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external tube 2nd end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
16 2nd end
Burst Test Pressure:
7500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Seat Angle:
45.0 degrees 2nd end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant
Inside Surface Condition:
Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 31.300 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A542a0