## NSN 4720-00-045-3407

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-045-3407 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.313 inches **Tempurature Rating:** 

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

**Outside Diameter:** 

0.466 inches

**Minimum Inside Bending Radius:** 

4.000 inches

**Connection Style:** 

Swivel nut flare 1st end

**End Connection Design:** 

Straight 1st end

**Connection Type:** 

Threaded internal tube 1st end

**Burst Test Pressure:** 

9000.0 pounds per square inch

**Layer Composition And Location:** 

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:** 

1500.0 pounds per square inch

**Thread Size:** 

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

**Hydrostatic Test Pressure:** 

3000.0 pounds per square inch

Vacuum In Torr:

50.8

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

48.000 inches working

**Thread Series Designator:** 

Unf 1st end

**Specification Data:** 

81349-mil-h-25579 government specification

## NSN 4720-00-045-3407

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0

Mil-std (military Standard):

Mil-h-25579 spec.