NSN 4720-00-045-9996

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-045-9996

Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.875 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response				
Outside Diameter:				
1.109 inches				
Minimum Inside Bending Radius:				
7.380 inches				
Angle Between Rigid Elbow Fittings In Deg:				
180.0				
Connection Style:				
Swivel nut flare 2nd end				
End Connection Design:				
Elbow 2nd end				
Connection Type:				
Threaded internal tube 1st end				
Thready Qty Per Inch (tpi):				
12 2nd end				
Burst Test Pressure:				
5000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
1250.0 pounds per square inch				
Thread Size:				
1.312 inches 2nd end				
Seat Angle:				
37.0 degrees 2nd end				
Hydrostatic Test Pressure:				
2500.0 pounds per square inch				
Flow Angle:				
90.0 degrees 2nd end				
Inside Surface Condition:				
Smooth				

30.000 inches working

Measuring Method And Length:

NSN 4720-00-045-9996

Nonmetallic Hose Assembly - Page 2 of 2



TL		Carias	Daalas	4
111	reau	Series	Design	iatoi.

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0