## NSN 4720-00-046-5498

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-046-5498

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Outside Diameter:
0.531 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal hose 1st end
Thready Qty Per Inch (tpi):
20 1st end
Burst Test Pressure:
1500.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided cotton cord
Maximum Operating Pressure:
275.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and mildew resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
22.875 inches working and 23.125 inches working
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4720-00-046-5498

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0