NSN 4720-00-050-0182

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-050-0182

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 260.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
6.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
2200.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1100.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
18.000 inches working
Thread Series Designator:
Unf 1st end
Specification Data:
96906-ms24548 government standard
Shelf Life:
N/a

NSN 4720-00-050-0182

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Meası

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-prf-26626 spec.