## NSN 4720-00-050-0493

**Cross Sectional Shape:** 

40.000 inches working

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-050-0493

Measuring Method And Length:
Smooth
Inside Surface Condition:
50.8
Vacuum In Torr:
90.0 degrees 2nd end
3000.0 pounds per square inch  Flow Angle:
Hydrostatic Test Pressure:
37.0 degrees 2nd end
Seat Angle:
0.438 inches 1st end
Thread Size:
1500.0 pounds per square inch
Maximum Operating Pressure:
Outer layer braided corrosion resistant steel wire
Layer Composition And Location:  Outer layer braided corrector resistant steel wire
12000.0 pounds per square inch
Burst Test Pressure:
Electrostatic discharge capability
Features Provided:
Threaded internal tube 1st end
Connection Type:
Straight 1st end
End Connection Design:
Swivel nut flare 2nd end
Connection Style:
2.000 inches
Minimum Inside Bending Radius:
0.312 inches
Outside Diameter:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Tempurature Rating:
0.188 inches
Inside Diameter:
Right-hand 1st end
Thread Direction:
3b 1st end
Thread Class:
Round

## NSN 4720-00-050-0493

Nonmetallic Hose Assembly - Page 2 of 2



Thread S	Series	Designator:
----------	--------	-------------

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0