Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-052-0929

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3a 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.437 inches |
| Outside Diameter: |
| 0.800 inches |
| Minimum Inside Bending Radius: |
| 8.000 inches |
| Connection Style: |
| External seat for gasket seal (boss) 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external boss 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Layer Composition And Location: |
| 2nd layer spirally laid corrosion resistant steel wire and outer layer braided corrosion resistant steel wire and 1st layer braided corrosion |
| resistant steel wire |
| Maximum Operating Pressure: |
| 4500.0 pounds per square inch |
| Thread Size: |
| 1.750 inches 1st end |
| Hydrostatic Test Pressure: |
| 9000.0 pounds per square inch |
| Criticality Code Justification: |
| Zzzy |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 20.500 inches |
| Thread Series Designator: |
| |
| Reference Number Differentiating Characteristics: |
| Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items |
| Shelf Life: |

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0