NSN 4720-00-052-3185

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-052-3185
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-100.0 degrees fahrenheit single response and 500.0 degrees fahrenheit single response
Outside Diameter:
0.312 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
2500 0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

4.250 inches working

Thread Series Designator:

Unf 2nd end

NSN 4720-00-052-3185

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

07482-r464c0042a manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0