Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-052-3187

View Online at https://aerobasegroup.com/nsn/4720-00-052-3187
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.625 inches
Tempurature Rating:
-100.0 degrees fahrenheit single response and 500.0 degrees fahrenheit single response
Bolt Circle Diameter:
1.635 inches 2nd end
Outside Diameter:
0.781 inches
Angle Between Rigid Elbow Fittings In Deg:
270.0
Bolt Hole Quantity:
4 1st end
Connection Style:
Swivel nut flare 1st end
Bolt Hole Diameter:
0.205 inches 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2500.0 pounds per square inch

NSN 4720-00-052-3187

Nonmetallic Hose Assembly - Page 2 of 2



Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

93.250 inches working

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0