

View Online at <https://aerobasegroup.com/nsn/4720-00-052-4829>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Outside Diameter:

1.010 inches

Hose Or Tubing Specification/std Data:

Zz-h-601, grade 1, class 2, size 1/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Connection Style:

Plain optional end 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Connection Type:

Threaded internal pipe 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

600.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic

Maximum Operating Pressure:

150.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Hydrostatic Test Pressure:

300.0 pounds per square inch

Outer Covering Environmental Protection:

Water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

12.000 inches working

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Water, fresh single response

Thread Series Designator:

Npt 1st end

Specification Data:

Zz-h-601, grade 1, class 2, size 1/2 professional/industrial association specification and 81348-zz-h-601 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0