Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-052-6425

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.190 inches	
Tempurature Rating:	
65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Outside Diameter:	
0.520 inches	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
20 2nd end	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated cotton fabri	c and 1st layer braided cotton cord
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 2nd end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Flow Angle:	
90.0 degrees 2nd end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
24.000 inches working	
Thread Series Designator:	
Unf 2nd end	
Shelf Life:	

## NSN 4720-00-052-6425

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0