NSN 4720-00-053-8678

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-053-8678

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Outside Diameter:
0.609 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Vacuum In Torr:
50.8
Criticality Code Justification:
Feat
Inside Surface Condition:
Smooth

15.800 inches working and 16.100 inches working

Measuring Method And Length:

NSN 4720-00-053-8678

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:
Design analysis; nuclear hardness critical
Special Markings:
Identification tape which reads to missile
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Nuclear Hardness Critical Feature:
Hardened
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A542a0