## NSN 4720-00-054-6358

Nonmetallic Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-054-6358

| view Online at https://aerobasegroup.com/hsn/4720-00   |
|--|
| Cross Sectional Shape:                                 |
| Round  |
| Inside Diameter:                                       |
| Between 0.735 inches and 0.781 inches                  |
| Tempurature Rating:                                    |
| -67.0 degrees fahrenheit single response               |
| Outside Diameter:                                      |
| Between 1.125 inches and 1.187 inches                  |
| Minimum Inside Bending Radius:                         |
| 9.500 inches   |
| Burst Test Pressure:                                   |
| 9000.0 pounds per square inch single response          |
| Layer Composition And Location:                        |
| 1st layer braided steel wire err-100                   |
| Maximum Operating Pressure:                            |
| 2250.0 pounds per square inch single response          |
| Hydrostatic Test Pressure:                             |
| 4500.0 pounds per square inch single response          |
| Outer Covering Environmental Protection:               |
| Mildew resistant and oil resistant and ozone resistant |
| Inside Surface Condition:                              |
| Smooth   |
| Measuring Method And Length:                           |
| 120.000 inches excluding end fittings                  |
| Material:  |
| Rubber synthetic tube                                  |
| Media For Which Designed:                              |
| Hydraulic fluid, silicate-ester base single response   |
| Specification Data:                                    |
| 81349-mil-h-13531 government specification             |
| Specification Or Standard:                             |
| 2 type and b class                                     |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                       |
|  |
| Demilitarization:                                      |
| No   |
| Fiig:  |

A541z0