NSN 4720-00-054-7774

Air Duct Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-054-7774

Cross Sectional Shape:

Cross Sectional Shape:
Round
Wall Thickness:
0.120 inches
Inside Diameter:
1.000 inches first end
Endlength:
1.250 inches first end
Connection Style:
Round first end
Connection Type:
Soft first end
Features Provided:
Stowage device
End Inside Diameter:
1.125 inches first end
Maximum Operating Pressure:
Maximum Operating Pressure: 3.0 pounds per square inch
3.0 pounds per square inch
3.0 pounds per square inch Measuring Method And Length:
3.0 pounds per square inchMeasuring Method And Length:10.800 inches
3.0 pounds per square inch Measuring Method And Length: 10.800 inches Material:
3.0 pounds per square inch Measuring Method And Length: 10.800 inches Material: Steel reinforcing wire
3.0 pounds per square inch Measuring Method And Length: 10.800 inches Material: Steel reinforcing wire Style Designator:
3.0 pounds per square inch Measuring Method And Length: 10.800 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported
3.0 pounds per square inch Measuring Method And Length: 10.800 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Shelf Life:
3.0 pounds per square inch Measuring Method And Length: 10.800 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Shelf Life: N/a
3.0 pounds per square inch Measuring Method And Length: 10.800 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Shelf Life: N/a
3.0 pounds per square inch Measuring Method And Length: 10.800 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure:
3.0 pounds per square inch Measuring Method And Length: 10.800 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Shelf Life: N/a Unit Of Measure: Demilitarization: