Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-054-8748

Cross Se	ctional Shape:
Round	
Thread C	lass:
3b 1st end	3
Thread D	irection:
Right-han	
Inside Dia	
0.188 inch	ies
Tempurat	ture Rating:
	rees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside [
0.312 incl	les
Minimum	Inside Bending Radius:
2.000 inch	ies
Connecti	on Style:
Swivel nu	t flare 1st end
End Con	nection Design:
Straight 1	st end
Connecti	on Type:
Threaded	internal tube 1st end
Burst Tes	st Pressure:
12000.0 p	ounds per square inch
Layer Co	mposition And Location:
Outer laye	er braided corrosion resistant steel wire
Maximum	n Operating Pressure:
100.0 pou	inds per square inch
Thread S	ize:
0.438 incl	nes 1st end
Seat Ang	le:
37.0 degr	ees 1st end
Hydrosta	tic Test Pressure:
3000.0 po	unds per square inch
Vacuum I	n Torr:
50.8	
Inside Su	rface Condition:
Smooth	
Thread S	eries Designator:
Unjf 1st ei	
Shelf Life	r:
N/a	
Unit Of M	easure:

NSN 4720-00-054-8748

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

