## NSN 4720-00-055-4940

**Cross Sectional Shape:** 

Unf 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-055-4940

Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.713 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
16 1st end
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber and 1st layer braided steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
13.250 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

## NSN 4720-00-055-4940

Nonmetallic Hose Assembly - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0