

View Online at <https://aerobasegroup.com/nsn/4720-00-055-6795>

**Cross Sectional Shape:**

Round

**Wall Thickness:**

Between 0.062 inches and 0.071 inches

**Connection Type:**

Coupling first end

**Thready Qty Per Inch (tpi):**

20 first end

**Maximum Operating Pressure:**

500.0 pounds per square inch

**Thread Size:**

0.500 inches first end

**Measuring Method And Length:**

32.962 inches

**Coupling Style:**

Threaded internal first end

**Special Features:**

Ozone resistance: not ozone resistant; end similarity: identical; inside dia.: 0.235 in. Min, 0.265 in. Max.; hose style: sleeve section, style no. 5 from old fig a22900; hose material: plastic tetrafluorethylene, steel (qq-s-763, class 304) and bdronze coated steel wire; communications cable and restraint cord: not included

**Material:**

Steel 1st end coupling

**Surface Treatment:**

Passivate 1st end coupling

**Thread Series Designator:**

Unjf first end

**Departure From Cited Document:**

32 in. Lg

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A229a0

**Mil-std (military Standard):**

Mil-prf-26626 spec.