NSN 4720-00-056-0163

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-056-0163

Between 0.477 inches and 0.570 inches			
Tempurature Rating:			
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response			
Outside Diameter:			
Between 0.718 inches and 0.789 inches			
Minimum Inside Bending Radius:			
3.500 inches			
Angle Between Rigid Elbow Fittings In Deg:			
0.0			
Connection Style:			
Swivel nut, flareless 1st end			
End Connection Design:			
Elbow 1st end			
Connection Type:			
Threaded internal tube 1st end			
Burst Test Pressure:			
1000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer molded rubber, chloroprene and 1st layer rubber impregnated braided fabric			
Maximum Operating Pressure:			
400.0 pounds per square inch			
Thread Size:			
0.750 inches 1st end			
Seat Angle:			
12.0 degrees 1st end			
Hydrostatic Test Pressure:			
600.0 pounds per square inch			
Flow Angle:			
90.0 degrees 1st end			
Outer Covering Environmental Protection:			
Fuel resistant and hydraulic solution resistant and mildew resistant and oil resistant and ozone resistant			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
67.625 inches working and 68.375 inches working			

NSN 4720-00-056-0163

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:	Thread	Series	Designator:
---------------------------	--------	---------------	--------------------

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0