

View Online at <https://aerobasegroup.com/nsn/4720-00-056-3694>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

0.578 inches

**Minimum Inside Bending Radius:**

3.375 inches

**Exterior Color:**

Black

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Burst Test Pressure:**

10000.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided steel wire and outer layer rubber impregnated braided fabric and 1st layer braided fiber

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.500 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

5000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Mildew resistant and oil resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

65.000 inches

**Media For Which Designed:**

Air and ethylene glycol and hydraulic fluid and fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0